



Hi-Temp titanium 40-75kW

Hi-Temp titanium is a spiral heat exchanger made of thermoplastic. With a coil of titanium for the most demanding installations where there is a high risk of corrosion, such as in pools with salt water or where a salt chlorinator is used.

Maximum pressure secondary circuit (pool water) is 4 bar and primary circuit (hot water) is 5 bar.



| Technical data | | Capacity | | | Primary, hot water | | Secondary, pool water | |
|----------------|--------|----------|--------|--------|--------------------|-------------------|-----------------------|-------------------|
| Item no. | Type | kW | kBtu/h | kcal | l/min | press. drop H (m) | l/min | press. drop H (m) |
| 11322 | HTT 40 | 40 | 135 | 34 393 | 52 | 1.5 | 300 | 1.1 |
| 11324 | HTT 75 | 75 | 260 | 64 488 | 58 | 2.5 | 300 | 1.2 |

Capacity at a temperature difference of 60°C

Hi-Temp 40-75kW

Hi-Temp is a spiral heat exchanger made of thermoplastic, and with a coil of acid proof stainless steel AISI 316L.

Maximum pressure secondary circuit (pool water) is 4 bar and primary circuit (hot water) is 5 bar.



| Technical data | | Capacity | | | Primary, hot water | | Secondary, pool water | |
|----------------|------|----------|--------|--------|--------------------|-------------------|-----------------------|-------------------|
| Item no. | Type | kW | kBtu/h | kcal | l/min | press. drop H (m) | l/min | press. drop H (m) |
| 11312 | HT40 | 40 | 135 | 34 393 | 34 | 1.9 | 300 | 1.3 |
| 11314 | HT75 | 75 | 260 | 64 488 | 43 | 5.5 | 300 | 1.7 |

Capacity at a temperature difference of 60°C